



Security screws specifically designed for metal siding and roofing applications

**TORX® PIN-HEAD**


Maximum torque transfer and positive tool engagement means easier drive installation with less pressure and slippage. Torx® Pin Head offers a high degree of security and requires matching drive bit. Available in button head for neat appearance and TRI-SEAL™ 1,000 hours salt spray coating for additional corrosion protection.



T-27 Torx Pin  
Recess Drive

**Does your building need security?**

- ▶ Mini Storage
- ▶ Prisons
- ▶ Government Buildings
- ▶ Banks
- ▶ Dealerships





Assembled with a BOND-SEALER™ sealing washer that has EPDM vulcanized to a 20 Gauge galvanized backing that will withstand harsh weather conditions.

**SIZES AND PERFORMANCE SPECIFICATIONS**

Size	Point Type	Drilling Thickness	Attachment Thickness	Box Quantity
A #12-14 x 2"	BLAZER 3	.036" - .210"	1"	2.0M
B #12-14 x 1-1/2"		.036" - .210"	.750"	2.0M
C 1/4-14 x 7/8"	BLAZER 1	.036" - .090"	.250"	2.5M

Blue colored sizes denotes popular DC items

To assure a proper seal, torque the fastener until the EPDM sealant extrudes to the outer edge of the backing material.



We supply insert bits to make installation fast and easy!

**MATERIAL:** C1018-1022 Carbon Steel  
**PLATING:** . TRI-SEAL™ 1,000 hours salt spray coating

**Pullout Test Result - Ultimate Average in Pounds**

Fastener Information		PULLOUT   ULTIMATE LOAD IN POUNDS												
		Grade 80 and Grade 50 Steel per ASTM A792/A1011/A653/A572/A529 Calculated Values In Accordance to AISI S100   Section E4												
Thread and Point Type	Nom Dia. (in.)	Grade 80 82Ksi Min.						Grade 50 65Ksi Min. Steel						
		26 Ga. (.018")	24 Ga. (.024")	22 Ga. (.030")	20 Ga. (.036")	18 Ga. (.048")	16 Ga. (.060")	14 Ga. (.075")	12 Ga. (.105")	1/8" (.125")	10 ga (.135")	1/4" (.250")	3/8" (.375")	1/2" (.500")
#12-14	.216"	205	286	358	430	573	716	895	1,253	1,492	1,611			
1/4-14	.250"	237	332	414	497	633	829	1,036	1,450					

The tensile strength of the substrate that is used in the chart is typical for metal building and roofing applications. Contact TFC if other substrate tensile strengths are required.

**Contact Triangle Fastener for additional sizes and types of security screws.**

DISCLAIMER: ALL TEST RESULTS AND SPECIFICATIONS ARE A RESULT OF LABORATORY TESTS. APPROPRIATE SAFETY FACTORS SHOULD BE USED BY THE USER OR SPECIFIER. DETERMINING THE PROPER FASTENER IS THE RESPONSIBILITY OF THE USER OR SPECIFIER. SINCE APPLICATION CONDITIONS VARY AND ARE UNCONTROLLABLE BY TFC, WE ASSUME NO LIABILITY FOR THE USE OF THIS INFORMATION.