

BUTYL TAPE-SEAL

BUTYL TAPE-SEAL

*Specially formulated
for use on metal roof
and wall panels.*

BUTYL TAPE-SEAL™ was designed specifically for the metal building industry to provide optimal sealing in the harshest environments.

It adheres to most clean, dry metal surfaces and does not harden, bleed or stain. With pressure, it fills minor irregularities in the surface and seals the joints providing an effective barrier against water, moisture, dust, and dirt.

BUTYL TAPE-SEAL™ is an excellent choice for use around windows, doors, roof vents, stacks, access doors, and other penetration points.



SIZES

Stocked sizes - Others available upon request

Size (T x W x L)	TFC P.N.	Rolls/ Ctns	Ctns/ Pallet
3/32" x 3/8" x 45'	0937BCT	48	30
3/32" x 1/2" x 50'	0950BCT	22	50
3/32" x 1" x 45'	0910BCT	24	30
1/8" x 1/2" x 50'	1250BCT50	13	48
1/8" x 1" x 50'	1210BCT50	8	48
3/16" x 1/4" x 40'	1825BCT	20	48
3/16" x 7/8" x 40' *DB	1887BCT	10	48
3/16" x 7/8" x 25' *TB	1887BCT25TRI	8	64
3/16" x 2-1/2" x 20' *TB	TC826W	6	60



*DB denotes double bead

*TB denotes triple bead

PACKAGING

BUTYL TAPE-SEAL™ is extruded butyl material with a silicone backed release paper that is rolled and cut to specific lengths.

Our master cartons are constructed of 200 pound test material and the rolls are separated by silicone divider pads and protected by upright stacking cores.



Easy to install!



Adheres to:

- Painted Metal
- Galvalume®
- Kynar®
- Aluminized Metal

CLEAN UP

Mineral spirits will readily facilitate the cleaning of tools and equipment.