

The largest selection for the construction industry!

Thin and Medium Gauge Applications | 29ga to 1/4"

BLAZER 1 - BLAZER 2 - BLAZER 3 Points



*High Hex or Serrations Available

Blue colored sizes denotes popular DC items



5/16" HWH



U.S. Pat. No. 8,360,701
Taiwan Pat No. I50140
Europe Pat No. 2286067



*Available in 5/16" and 3/8" HWH



Sliding Rake Angle Screw
SSR Clip | 5/16" HWH



Want a screw that takes more force before bending?

Our NEW 5/16" diameter is 5-1/2 times stiffer than a 1/4-14 drill screw.

- The hex washer head is the most popular drive system and provides the best stability during installation.
- Available with TRI-SEAL® long life coating for the ultimate corrosion protection...1,000 hrs salt spray with no red rust!

SIZES AND PERFORMANCE SPECIFICATIONS

	Diameter Length	Load Bearing Length (MAX)	Box Qty	Point Type	Drilling Thickness	
A	#8-18 x	1/2"	.100"	10M	BLAZER 2	.036" .100"
		5/8"	.125"	10M		
		3/4"	.250"	10M		
		1"	.500"	7.5M		
		1-1/4"	.750"	5M		
		1-1/2"	1"	5M		
B	#10-16 x	1/2"	.100"	10M	BLAZER 3	.036" .175"
		5/8"	.125"	5M		
		5/8" HH	.125"	5M		
		3/4"	.250"	5M		
		3/4" HH/SERR	.250"	5M		
		1"	.500"	5M		
		1-1/2"	1"	3.5M		
		2"	1.500"	2M		
		3"	2.500"	1M		
		3"	2.500"	1M		
C	#12-14 x	3/4"	.125"	5M	BLAZER 3	.036" .210"
		1"	.250"	3.5M		
		1-1/4"	.625"	3M		
		1-1/2"	.750"	2M		
		2"	1.25"	2M		
		2-1/2"	1.75"	1M		
		3"	2.25"	1M		
		4" HWH	3.75	500		
D	1/4-14 x	7/8" VRT	.325"	2.5M	BLAZER 1/VRT	.036" .090"
		3/4"	.125"	2.5M	BLAZER 3	.036" .250"
		1"	.250"	2.5M		
		1-1/4"	.625"	2M		
		1-1/2"	.875"	2M		
		2"	1"	1.5M		
		2-1/2"	1.50"	1M		
		3"	2"	1M		
		4"	3"	500		
		5"	4"	500		
		6"	2" - 5"	250		
		8"	4" - 7"	250		
10"	6" - 9"	250				
E	1/4-14 x	1-1/4"	.625"	3.5M	BLAZER 3 SHLDR	.036" .210"
		1"	.250"	1.5M		
G	5/16-12 x	1-1/2"	.875"	1M	BLAZER 3	.036" .210"
		3"	2.25"	750		
		4"	3.25"	500		
		6"	2.50 - 5"	500		
		8"	4.25" - 7"	200		
		8"	4.25" - 7"	200		
H	#12-24 x	7/8"	.325"	5M	BLAZER 4	.125" .250"
		1-1/4"	.500"	3M	BLAZER 4.5	.125" .375"
I	#12-24 x	1-1/4"	.500"	3M	BLAZER 5	.125" .500"
		1-1/2"	.625"	2M		
		2"	.750"	3M		
		2"	.750"	3M		
J	1/4-20 x	1-1/2"	.500"	2M	BLAZER 5	.200" .500"
		2-1/4"	1.250"	1M		
		3-1/8"	2.125"	500		
		4"	3"	250		
		5"	4"	250		
		8"	2.50" - 5"	250		
8"	4.25" - 7"	150				

Heavy Gauge Applications | 1/4" to 1/2"

BLAZER 4 & BLAZER 5 Points

- Drill and tap up to 1/2" thick steel.
- Supplied with our TRI-SEAL® long life coating for superior corrosion protection.
- Lengths up to 8" for retrofit metal roof base attachment.



HEX DRIVE SIZE

#8 dia: 1/4" HWH

#10 dia: 5/16" HWH

#12 dia: 5/16" HWH

1/4 dia: 5/16" & 3/8" HWH

5/16 dia: 3/8" HWH



All screws are available with Bonded Sealing Washers. Call for sizes

MATERIAL: C1018-1022 Carbon Steel

PLATING: .0003" Minimum Zinc Plated (48 hrs salt-spray)

Long-Life: TRI-SEAL® Coating (1,000hrs Salt Spray - ASTM B117).

Exceeds ASTM B633 and F1941 Standards

Dimensions: Meets or exceeds SAE J78 Standards