

**The largest selection for the construction industry!**

**Thin and Medium Gauge Applications | 29ga to 1/4"**

**BLAZER 1 - BLAZER 2 - BLAZER 3 Points**



\*High Hex or Serrations Available

Blue colored sizes denotes popular DC items



5/16" HWH



U.S. Pat. No. 8,360,701  
Taiwan Pat No. I50140  
Europe Pat No. 2286067



\*Available in 5/16" and 3/8" HWH



Sliding Rake Angle Screw  
SSR Clip | 5/16" HWH



**Want a screw that takes more force before bending?**

**Our NEW 5/16" diameter is 5-1/2 times stiffer than a 1/4-14 drill screw.**

- The hex washer head is the most popular drive system and provides the best stability during installation.
- Available with TRI-SEAL® long life coating for the ultimate corrosion protection...1,000 hrs salt spray with no red rust!

**SIZES AND PERFORMANCE SPECIFICATIONS**

	Diameter   Length	Attachment Thickness	Box Qty	Point Type	Drilling Thickness
A	#8-18 x 1/2"	.100"	10M	BLAZER 2	.036" .100"
	5/8"	.125"	10M		
	3/4"	.250"	10M		
	1"	.500"	7.5M		
	1-1/4"	.750"	5M		
	1-1/2"	1"	5M		
B	2"	1.5"	1.5M	BLAZER 3	.036" .175"
	1/2"	.100"	10M		
	5/8"	.125"	5M		
	5/8" HH	.125"	5M		
	3/4"	.250"	5M		
	3/4" HH/SERR	.250"	5M		
	1"	.500"	5M		
C	1-1/2"	1"	3.5M	BLAZER 3	.036" .210"
	2"	1.500"	2M		
	3"	2.500"	1M		
	3/4"	.125"	5M		
	1"	.250"	3.5M		
	1-1/4"	.625"	3M		
	1-1/2"	.750"	2M		
D	2"	1.25"	2M	BLAZER 3	.036" .210"
	2-1/2"	1.75"	1M		
	3"	2.75"	1M		
	4" HWH	3.75	500		
	1/4-14 x 7/8" VRT	.325"	2.5M		
	3/4"	.125"	2.5M		
	1"	.250"	2.5M		
E	1-1/4"	.625"	2M	BLAZER 3	.036" .250"
	1-1/2"	.875"	2M		
	2"	1"	1.5M		
	2-1/2"	1.50"	1M		
	3"	2"	1M		
	4"	3"	500		
	5"	4"	500		
F	6"	2" - 5"	250	BLAZER 3 SHLDR	.036" .210"
	8"	4" - 7"	250		
	10"	6" - 9"	250		
	1/4-14 x 1-1/4"	.750"	3.5M		
	1"	.250"	1.5M		
	1-1/2"	.875"	1M		
	3"	2.25"	750		
G	4"	3.25"	500	BLAZER 3	.036" .210"
	6"	2.50 - 5"	500		
	8"	4.25" - 7"	200		
	7/8"	.325"	5M		
H	#12-24 x 1-1/4"	.500"	3M	BLAZER 4	.125" .250"
	1-1/4"	.500"	3M	BLAZER 4.5	.125" .375"
I	#12-24 x 1-1/4"	.500"	3M	BLAZER 5	.125" .500"
	1-1/2"	.625"	2M		
	2"	.750"	3M		

**Heavy Gauge Applications | 1/4" to 1/2"**

**BLAZER 4 & BLAZER 5 Points**

- Drill and tap up to 1/2" thick steel.
- Supplied with our TRI-SEAL® long life coating for superior corrosion protection.
- Lengths up to 8" for retrofit metal roof base attachment.



**HEX DRIVE SIZE**

- #8 dia: 1/4" HWH
- #10 dia: 5/16" HWH
- #12 dia: 5/16" HWH
- 1/4 dia: 5/16" & 3/8" HWH
- 5/16 dia: 3/8" HWH



All screws are available with Bonded Sealing Washers. Call for sizes

**MATERIAL:** C1018-1022 Carbon Steel  
**PLATING:** .0003" Minimum Zinc Plated (48 hrs salt-spray)  
**Long-Life:** TRI-SEAL® Coating (1,000hrs Salt Spray - ASTM B117). Exceeds ASTM B633 and F1941 Standards  
**Dimensions:** Meets or exceeds SAE J78 Standards