



POLYMER GYPTEC AUGERS Fast Facts

A glass-filled nylon auger fastener with a 1" head designed to secure insulation and single-ply membrane to gypsum, all cementitious wood fiber, Tectum® and certain lightweight concrete decks.

PHYSICAL DATA	CAT. NO.	LENGTH	PACKAGING	WEIGHT
The data below is constant for each Olympic NTB-1HWO	NTB1025WO	2 1/2"	500	13 lb.
	NTB1030WO	3"	500	15 lb.
	NTB1035WO	3 1/2"	500	17 lb.
Head Size: 1" Diameter	NTB1040WO	4"	500	19 lb.
	NTB1045WO	4 1/2"	500	21 lb.
Head Style: Double Internal Hex Drive	NTB1050WO	5"	500	24 lb.
	NTB1055WO	5 1/2"	500	26 lb.
	NTB1060WO	6"	500	28 lb.
Major Thread Diameter: .750	NTB1065WO	6 1/2"	500	29 lb.
	NTB1070WO	7"	500	30 lb.
Thread: 3.5 T.P.I. Buttress	NTB1075WO	7 1/2"	500	32 lb.
	NTB1080WO	8"	250	16 lb.
Material: Glass-Filled Nylon	NTB1085WO	8 1/2"	250	17 lb.
	NTB1090WO	9"	250	18 lb.
	NTB1095WO	9 1/2"	250	19 lb.
	NTB1100WO	10"	250	20 lb.

Features & Benefits

- Thread design & large root diameter:
 - Increase pullout resistance
 - Increase side shear strength
- Made from glass-filled nylon which:
 - Eliminates corrosion
 - Eliminates thermal bridging and condensation
 - Yields high tensile strength
- F.M. and MIAMI-Dade approved.

Plates & Accessories

Use 3" steel plate, 2" steel plate (with barbs), or batten bar.

Use a carbide tip drill bit for gypsum, lightweight concrete and some cementitious wood fiber applications.