



## TRACER® D.S. Pan Framer

Attachment of steel stud of steel track or for splicing steel stud up to 14 gauge (.075") total thickness.

Size/Length	Carton Quantity (M)
6 x 7/16"	10
8 x 1/2"	10
8 x 1"	10

.00015" zinc plated zinc plated



## TRACER® D.S. Round Washer Head

Attachment of wood trim thru drywall to steel stud up to 14 gauge (.075").

Size/Length	Carton Quantity (M)
8 x 1/2"	10
8 x 3/4"	5
8 x 1 1/4"	10

.00015" zinc plated zinc plated



## BLAZER® Pan Head

Fastener for steel framing applications.

Size/Length	Head Type
8-16 x 5/8" DP2	Phillips pan

.00015" zinc plated zinc plated



## BLAZER® Lo Profile Pancake Head

Fastener for steel framing applications.

Size/Length	Head Type
10-16 x 5/8" DP3	#2 square recess

.0003" zinc and yellow



## BLAZER® Lo Profile High Torq Pancake Head #2 Sq.

Fastener for steel framing applications.

Size/Length	Head Type
10-24 x 5/8" DP3	#2 Sq.Phil recess

.0003" zinc and yellow



## BLAZER® Hi-Hex

Fastener for steel framing applications. With serration.

Size/Length	Head Type
10-16 x 5/8" DP3	5/16" Hi-Hex

.0003" zinc plated



## BLAZER® Heavy Gauge

Fastener for steel framing applications.

Size/Length	Head Type
12-24 x 1 1/4" DP5	5/16" HWH

.0003" zinc plated with long life coating.



## \*EXTERIOR USE

## BURR-BUSTER® Self-Piercing

For exterior applications. Pierce up to 20 ga. steel.

Size/Length	Head Type
#10-16 x 3/4"	5/16" HWH

Finish: TRI-SEAL® Long Life Coating  
Corrosion results: 1,000 hrs. salt spray  
Applications: Pierce and tap up to 20 ga.



## STRESS-LESS® Framing Screw

Fastener for steel framing applications with high stress concentrations. Drill and tap up to 1/4" steel!

Size/Length	Head Type
1/4-14 x 7/8" DP3	5/16" Hex washer head
Epoxy Coated	

For technical data, refer to page 12.