

# FIX-A-FLASH

*Our New Large-base Flashing Specifically Designed to Seal Oversized Holes in Your Roof!*

The PIPE-MASTER FIX-A-FLASH flashing has a 19½ square base; perfect for sealing oversized holes around your pipe penetrations.



### Large Base Dimension

The base is designed to cover an oversized hole around your penetration.

### Weather Protection

Made of E.P.D.M. or Silicone; These flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.

### Flash Penetration

Holes up to 16" wide.

*20-year warranty!*

### DIMENSIONS

Pipe size = Up to 15" diameter

Base size = 19½". Flash up to 16" wide

### SPECIFICATIONS

|                             | EPDM                | Silicone            |
|-----------------------------|---------------------|---------------------|
| Advanced Ozone Resistance   | 70 hours @ 500 pphm | 70 hours @ 500 pphm |
| High Temperature Resistance |                     |                     |
| Intermittent                | +135° C (275° F)    | +260° C (+500° F)   |
| Continuous                  | +100° C (212° F)    | +225° C (+437° F)   |
| Low Temperature Resistance  | -55° C (65° F)      | -74° C (-100° F)    |
| Tensile Strength (min)      | 10 MPa (1450 psi)   | 5 MOPa (700 psi)    |
| Compression Set (max)       | 25%                 | 50%                 |

### INSTALLATION TIPS



### Fastening Recommendation

Corrosion resistant fasteners should be used around the base one every 1-1/2 inches as per the United Plumbing Code (UPC) recommendations.

- Fastener  
1/4-14 x 1-1/8" DP1 BLAZER Stainless Cap Head with VRT Technology



### Sealant Recommendation

Ultra 1000® or APS 500 sealant should be used under the base to assure a proper seal. If you prefer, additional sealant can be applied around base after installation.