



# SPAX® PowerLags®

**T-STAR WASHER HEAD**

Offers a low profile option for outstanding clamping force with improved aesthetics. (Shown with yellow zinc coating for interior use.)

**BUILT-ON WASHER**

Head design eliminates need for a separate washer.

**PATENTED SERRATIONS**

Require up to 40% less driving torque.

**NO PRE-DRILLING**

Allows for faster, easier installation.

*Premium wood screw now available for the commercial construction industry.*

TFC offers SPAX® screws with it's patented thread form that eliminates the need for pre-drilling wood!

- Patented thread reduces driving torque up to 40%.
- Installs with ordinary battery tools.
- Six Lobbed recess for superior driving stability.
- Heat treated to grade 5 specifications for superior strength
- HCR coated for exterior use.

## SIZES



## T-STAR WASHER POWER LAGS

Diameter and Length	Thread Length	Drive Type	Head Diameter	Head Height	Qty Per Bucket
1/4 x 3"	1.790"	T-30	.697"	.097"	500
1/4 x 3-1/2"	1.960"				
1/4 x 4"	2.335"				
5/16 x 3-1/2"	2.050"	T-40	.776"	.140"	250
5/16 x 4"	2.245"				



SPAX® screws are available in a wide array of sizes for most wood connections, including Hex Washer Head. Provides maximum driver engagement, especially when using larger diameter/ longer length parts in harder wood species.

## PERFORMANCE

Per ICC-ES Report Number ESR-1782

DIAMETER	ALLOWABLE STRENGTHS		SYP		DOUGLAS FIR		HEM-FIR & SPRUCE-FIR	
	TENSILE	SHEAR	PULLOUT	PULL THROUGH	PULLOUT	PULL THROUGH	PULLOUT	PULL THROUGH
1/4"	1,168	766	248	559	255	483	212	376
5/16"	1,459	920	295	602	259	495	210	375
3/8"	2,402	1,435	361	787	317	643	254	484
1/2"	3,404	2,394	392	946	345	807	279	327

Contact TFC for your specific needs.