

## ZAMAC™ Drive Pin Anchor


The TFC ZAMAC™ is a nail-in drive anchor which has a body formed from zinc alloy. Nails are available in carbon or stainless steel.

The anchor can be used in concrete, block, brick or stone.

Great for attacking termination bars attachment!



Mushroom Head Zamac Nailin®  
Carbon Steel Nail or 304SS Nail



Flat Head Zamac Nailin®  
Carbon Steel Nail

Diameter	Length	Pieces/ Box	Pieces/ Carton.	Price/ 100
3/16	7/8"	100	500	
1/4	1"	100	500	
1/4	1-1/4"	100	500	
1/4	1-1/2"	100	500	
1/4	2"	100	500	

### Performance Data

DIA.	EMBED. DEPTH	2,000 PSI Concrete		4,000 PSI Concrete		6,000 PSI Concrete		C-90 Hollow Block		Red Solid Block	
		TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR	TENSION	SHEAR
1/4"	5/8"	480	1230	600	1500	640	1500	360	1040	570	1250
	3/4"	580	1230	720	1500	760	1500	480	1160	790	1400
	7/8"	770	1350	820	1500	890	1500				
	1"							590	1320	820	1400
	1 1/8"	890	1400	960	1500	1060	1500				
	1 3/8"	980	1400	1150	1500	1230	1500	800	1320	950	1400
	1 7/8"	1150	1400	1300	1500	1365	1500				

DISCLAIMER: All information is non-binding and without guarantee. Before using the products, all specifications and calculations must be checked by a suitably qualified person and local regulations must be observed. This document is subject to revision. We reserve the right to make technical changes. (0321-1)