



# ULTRA1000®

## CLASS 35 | SILICONE SEALANT

Concerned about sealant failure caused by joint movement? Specify ULTRA1000™ Class 35 Silicone Sealant. It is formulated to withstand more joint movement than ordinary Class 25 sealants.

### Formulated for Superior Performance



- Silicone sealant provides exceptional weatherability
- Class 35 for superior movement capability
- Adheres to Kynar® and Galvalume® coated metals
- VOC compliant
- Mildew resistant
- "Guns" down to 0°F
- Service temperature -40°F to 350°F
- Tack free in 10 minutes
- 100% Silicone

### Bonds To



### Applications

- Flashing
- Trim
- Metal Sheeting
- Downspouts
- Gutters
- Roof Tile
- Flashings
- Adheres to Copper

APPROXIMATE\* LINEAR FEET/COVERAGE  
PER 10.1 FL. OZ. CARTRIDGE (298 ML)

		WIDTH							
DEPTH	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"	
	99	49	33	24	20	16	14	12	
	1/4"		24	20	12	10	8	7	6
	3/8"			11	8	6	5	5	4
	1/2"				6	5	4	3	3

### Packaging




**Never misplace another nozzle!**  
Tubes are now packaged with nozzle.


We've redesigned the packaging so that the plastic screw-on nozzles come pre-assembled on the tubes.




**20 Colors! Call for availability.** \*Denotes in stock colors




\*Translucent  
TR99



\*White  
WH100




\*Antique White  
WH102



\*Off White  
WH104




\*Black  
BLK110




\*Brown  
BR121




\*Dark Bronze  
BZ131




\*Red  
RD141




Regal Red  
RD143



\*Almond  
BG151



\*Sandstone  
BG152




\*Sierra Tan  
BG154



\*Hartford Green  
GR160




\*Green  
GR164




Hemlock Green  
GR161




\*Regal Blue  
BL181




\*Electric Blue  
BL182




\*Light Gray  
GY190



\*Slate Gray  
GY192



\*Charcoal Gray  
GY195



\*Gutter Gray  
GY196

NOTE: Colors listed do not represent actual colors. Contact your local distributor for the ULTRA1000® color selector swatches for accurate color match.

DISCLAIMER: All information is non-binding and without guarantee. Before using the products, all specifications and calculations must be checked by a suitably qualified person and local regulations must be observed. This document is subject to revision. We reserve the right to make technical changes. (0321-1)

**TRIANGLE FASTENER CORPORATION**

**800.486.1832 | [www.trianglefastener.com](http://www.trianglefastener.com)**

Visit our website for the most up-to-date product and technical information!

MD213.0523